



The SDQ5 loudspeaker design will definitely become an established value in the contactor market!

Its discrete design is in perfect harmony with the transparent sound exhibited.

The loudspeaker is equipped with a U-bracket. As the SDQ5 has the 1 step protection guard build-in, the loudspeaker is protected from overloads. This all makes the SDQ5 loudspeaker suited for dispersion of backgroundmusic and microphone calls.

The SDQ5 loudspeakers are available in 3 different colours: black (Ref; SDQ5-BL), white (Ref; SDQ5-W) and silver (SDQ5-SLV). As an option, the SDQ5 loudspeakers can be painted in any RAL colour (Ref; PAINT-CAB6). Please note that the minimum order quantity for PAINT-CAB6 is 12 pieces.

TECHNICAL SPECIFICATIONS

Type	2-way HiFi Pro, sealed box
Cabinet	Enforced poly plastic
Woofer	5.25" CP type
Tweeter	1" mylar ferro cooled
Impedance	8 Ohm
RMS Power 8 Ohm	
AES Rated	70 watt
Music - Program	100 watt
Dynamic Peak (lo-cut)	250 watt
Protection system	Auto-Reset 1 Guard
SPL 1 watt/1 m	91 dB
SPL Max peak	115 dB
Frequency Range	70 Hz - 20 kHz
Speaker connectors	Push terminals
Dispersion	120° H x 100° V
IP rating	50
Dimensions (H x W x D)	244 x 179 x 154 mm
Weight	2.07 Kg