

## ARTSERIES →



## PASSIVE SPEAKER

# ART 315i

RCF ART 315i is a wide dispersion, 2 way sound reinforcement speaker. It integrates a high power LICC high level crossover network and RCF low distortion, high power transducers. The result is a compact, high power accurate system, unique in its class for clarity and low distortion.

The new 15" inch woofer is the result of the latest refinement in years of RCF experience in compact 2 way speaker manufacturing, resulting in an accurate reproduction of the midbass frequency range and a tight punchy bass.

The compression driver uses a new 1.5" titanium dome in front of a low compression, optimised geometry, radial phase plug. This innovative design is powered from a high flux neodymium magnet and offers a very open and natural midrange sound and extreme precision in high frequency reproduction.

Our LICC low impedance compensated crossover network featuring lower (than conventional) induction value in series with the woofer offer delay reduction, reduced phase shift and superior transient response. The compression driver is protected by a fast dynamic electronic circuit.

The input section presents 2 x NL4 Speakon® connectors offering an easy loop-through link.

All components are housed in a strong, lightweight, polypropylene composite enclosure. Woofer and compression driver throat are protected from a strong, powder coated, metal grille. The cabinet features four M10 threaded fly points, a 35 mm pole mount adaptor two side handles and an ergonomic top handle.

### Applications

ART 315-i, ideal for any installation, offer the same careful acoustic design and innovative transducers used in the active series. Very good bass reproduction and extremely accurate high frequencies, ART 315-i is the perfect solution for playback and installation situations where an external amplifier is required.

### Features

- 300 watt power handling
- 128 dB SPL peak
- Wide dispersion, 90°x60° low distortion, constant directivity horn
- 15" high power woofer, 64mm edge wound aluminium coil
- 1" neodymium, titanium dome, high frequency driver
- LICCTM low impedance compensated crossover, electronic driver protection
- 2 x NL4 Speakon® connector
- 2 side handles and 1 ergonomic top handle for easy transportation and positioning

### ACOUSTICAL SPECIFICATIONS

Frequency response:	50 - 20 KHz
Max SPL:	128 dB
Sensitivity 1w/1m:	98
Coverage angle:	90° x 60°
Compression driver:	neo 1"
Woofer:	15"
Power handling:	300W

### INPUT SECTION







Input signal (Impedance):	8 ohm
Input connector:	speakon
Output signal connector:	speakon

### PROCESSOR SECTION


Crossover frequencies:	1800 Hz
Protections:	electronic

### PHYSICAL


Cabinet:	Composite PP
Dimensions (HxWxD):	26.77" x 15.94" x 13.58" (680x405x345 mm)
Weight:	37.48 lbs. (17 kg)
Hardware:	4 M10 flying points
Handles:	2 side, 1 top
Pole Mount / Cap:	yes
Colour:	Anthracyte gray



### Horizontal 1/3 Polar Plot



### Vertical 1/3 Polar Plot



CSI PRODUCT SPECIFICATIONS FOR DESIGNERS, SPECIFIERS, AND CONSULTANTS (ALSO KNOWN AS “A&E SPECIFICATIONS”) The following are “Part 2 Products” CSI-type specifications. It is assumed that “Part 1 General – Administrative and Procedures” and “Part 3 Execution – Installation and Maintenance” are part of an overall audio system or project specification.  
PART 2 PRODUCTS

### 2.01 Approved Manufacturer/Product

A. RCF, Via Raffaello 13, 42010 Mancasale, Reggio Emilia, Italy.

B. Model number: ART 315i

### 2.02 Design

Configuration	Compact 2 way speaker
LF Sub-section	15" woofer, 64 mm edge wound aluminium coil
HF Sub-section	1" neodymium

### 2.03 Acoustical Proprieties


Nominal dispersion angle:	Horizontal: 90° - Vertical: 60°
Axial frequency range:	50Hz-20kHz

### 2.04 Physical Properties

Cabinet:	Composite PP
Rigging inserts:	4 M10 fly points and built in pole mount adaptor
Color:	Anthracite gray
Grille:	Custom perforated steel grille with open-cell poly fiber backing
Input Connectors:	Speakon
Dimensions (H x W x D):	26.77" x 15.94" x 13.58" (680x405x345 mm)
Weight:	37.48 lbs. (17 kg)

### 2.05 Accessories

AC S260	Steel speaker floor stand with folding base end telescopic rod, tube Ø 35 mm
AC S140	Alluminium speaker floor stand with folding base end telescopic rod, tube Ø 35 mm
ART V-BR	Bracket for mounting one ART speaker on the wall - vertical. Adjustable inclination. Colour black.
ART H-BR	Bracket for mounting one ART speaker on the wall - horizontal. Adjustable inclination. Colour black.



RCF SpA Italy:  
tel. +39 0522 274 411  
fax +39 0522 232 428  
www.rcfaudio.com  
e-mail: info@rcf.it

RCF UK Sales Office:  
tel. +44 7005 402181  
e-mail: info@rcfaudio.co.uk

RCF France Sales Office:  
tel. +33 6 07501800  
e-mail: rcfrance@aol.com

RCF Germany Sales Office:  
tel. +49 2203 925370  
e-mail: germany@rcf.it

RCF USA Sales Office:  
tel. +1 (603) 926 4604  
e-mail: rcf-usa@comcast.net